SAFETY DATA SHEET

1. Identification

Product identifier 0125-0048 ORANGO-WET 1049740002

Other means of identification

Product code 1000016547
Recommended use CLEANER
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Avmor Ltd. Dept. Des Enregis Trement

Address 950 Michelin

Laval, QC H7L 5C1

Canada

TelephoneNot available.E-mailNot available.

Emergency phone number Emergency - US 1-866-836-8855

Emergency - Outside US 1-952-852-4646

Supplier Not available.

2. Hazard(s) identification

Physical hazardsFlammable aerosolsCategory 1Health hazardsSkin corrosion/irritationCategory 2Sensitization, skinCategory 1

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. Causes skin irritation. May cause an allergic skin reaction.

Precautionary statement

Prevention Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Contaminated work clothing should not be

allowed out of the workplace. Avoid release to the environment. Wear protective gloves.

Response IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical

advice/attention. Take off contaminated clothing and wash it before reuse. Collect spillage.

Storage Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Environmental hazards Hazardous to the aquatic environment, acute Category 1

hazard

Hazardous to the aquatic environment, Category 1

long-term hazard

Other hazards None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
d-Limonene		5989-27-5	30 - 60

Chemical name	Common name and synonyms	CAS number	%
Isobutane		75-28-5	15 - 40
Ethyl Alcohol		64-17-5	7 - 13
Propane		74-98-6	5 - 10
Other components below	reportable levels		0.1 - 1

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Remove contaminated clothing immediately and wash skin with soap and water. In case of Skin contact

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Rinse with water. Get medical attention if irritation develops and persists. Eye contact

In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth. Ingestion

Most important

symptoms/effects, acute and delayed

Provide general supportive measures and treat symptomatically. Keep victim under observation.

Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Indication of immediate medical attention and special treatment needed

General information

Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media

Water spray. Alcohol resistant foam. Powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA,

Fire fighting

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

equipment/instructions

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Use water spray to cool unopened

containers. In the event of fire and/or explosion do not breathe fumes.

General fire hazards Extremely flammable aerosol.

Accidental release measures

Personal precautions. protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent entry into waterways, sewer, basements or confined areas. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes, skin, and clothing. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

119	ACGIH	Thresho	I NI	imit \	عمداد/
UJ.	ACGILI	HIHESHU	nu Li		alues

US. ACGIH Threshold Limit Values Components	Туре	Value
Ethyl Alcohol (CAS 64-17-5)	STEL	1000 ppm
Isobutane (CAS 75-28-5)	STEL	1000 ppm
Canada. Alberta OELs (Occupation	nal Health & Safety Code, Sch	nedule 1, Table 2)
Components	Туре	Value
Ethyl Alcohol (CAS 64-17-5)	TWA	1880 mg/m3
		1000 ppm
Propane (CAS 74-98-6)	TWA	1000 ppm
Safety Regulation 296/97, as amen Components Ethyl Alcohol (CAS 64, 17, 5)	Туре	Value
Components Ethyl Alcohol (CAS 64-17-5)	Type STEL	1000 ppm
Components Ethyl Alcohol (CAS 64-17-5) Canada. Manitoba OELs (Reg. 217)	Type STEL /2006, The Workplace Safety	1000 ppm And Health Act)
Components Ethyl Alcohol (CAS 64-17-5) Canada. Manitoba OELs (Reg. 217)	Type STEL	1000 ppm
Components Ethyl Alcohol (CAS 64-17-5) Canada. Manitoba OELs (Reg. 217) Components	Type STEL /2006, The Workplace Safety	1000 ppm And Health Act)
Components Ethyl Alcohol (CAS 64-17-5)	Type STEL /2006, The Workplace Safety Type	1000 ppm And Health Act) Value
Components Ethyl Alcohol (CAS 64-17-5) Canada. Manitoba OELs (Reg. 217) Components Ethyl Alcohol (CAS 64-17-5) Isobutane (CAS 75-28-5)	Type STEL /2006, The Workplace Safety Type STEL STEL	1000 ppm And Health Act) Value 1000 ppm 1000 ppm
Components Ethyl Alcohol (CAS 64-17-5) Canada. Manitoba OELs (Reg. 217) Components Ethyl Alcohol (CAS 64-17-5)	Type STEL /2006, The Workplace Safety Type STEL STEL	1000 ppm And Health Act) Value 1000 ppm 1000 ppm
Components Ethyl Alcohol (CAS 64-17-5) Canada. Manitoba OELs (Reg. 217) Components Ethyl Alcohol (CAS 64-17-5) Isobutane (CAS 75-28-5) Canada. Ontario OELs. (Control of	Type STEL /2006, The Workplace Safety Type STEL STEL STEL Exposure to Biological or Cl	1000 ppm And Health Act) Value 1000 ppm 1000 ppm

Components Type Value

Ethyl Alcohol (CAS 64-17-5)	TWA	1880 mg/m3
		1000 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m3
		1000 ppm

Biological limit values Appropriate engineering controls

No biological exposure limits noted for the ingredient(s).

Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Face shield is recommended. Wear safety glasses with side shields (or goggles). Eye/face protection

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an

air-supplied respirator.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state Gas.
Form Aerosol.
Color Not available.
Odor Not available.
Odor threshold Not available.
PH Not available.
Melting point/freezing point Not available.

Initial boiling point and boiling

209.78 °F (98.76 °C) estimated

range

Flash point -156.0 °F (-104.4 °C) PROPELLANT estimated

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

1.3 % estimated

(%)

Flammability limit - upper

6.1 % estimated

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Explosive properties Not explosive. **Oxidizing properties** Not oxidizing.

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoidAvoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials
Hazardous decomposition
products

Strong oxidizing agents. Nitrates. Fluorine. Chlorine. No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation No adverse effects due to inhalation are expected.

Skin contact

Causes skin irritation. May cause an allergic skin reaction.

Eye contact

Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis.

Rash.

Information on toxicological effects

Acute toxicity May cause an allergic skin reaction.

Acute Oral LD50 Rat Season	Components	Species	Test Results
Oral LD50 Rat > 2000 mg/kg Ethyl Alcohol (CAS 64-17-5) Acute inhalation 85.41 mg/l, 4.5 Hours LC50 Cat 85.41 mg/l, 4.5 Hours LC50 Cat 85.41 mg/l, 4.5 Hours 43.68 mg/l, 6 Hours 60000 ppm 79.43 mg/l, 134 Minutes 79.43 mg/l, 14 Hours Pat > 115.9 mg/l, 6 Hours None LD50 Monkey 6000 mg/kg Mouse 10500 m/kg 10500 m/kg Pig > 5000 mg/kg 2000 mg/kg Isobutane (CAS 75-28-5) 25000 mg/kg 10470 mg/kg Acute inhalation 237 mg/l, 120 Minutes 25 %, 120 Minutes LC50 Rat 1237 mg/l, 120 Minutes 25 %, 120 Minutes LC50 Rat 1237 mg/l, 120 Minutes 25 %, 120 Minutes LC50 Mouse 1237 mg/l, 120 Minutes 26 %, 120 Minutes LC50 Mouse 1237 mg/l, 120 Minutes 26 %, 120 Minutes LC50 Mouse 1237 mg/l, 120 Minutes 26 %, 120 Minutes	d-Limonene (CAS 5989-27-5)		
LD50	<u>Acute</u>		
Ethyl Alcohol (CAS 64-17-5) Acute Inhalation	Oral		
Acute Inhalation LOSO	LD50	Rat	> 2000 mg/kg
Inhalation	Ethyl Alcohol (CAS 64-17-5)		
LC50	<u>Acute</u>		
Mouse Mouse A3.68 mg/l, 6 Hours			
Mouse	LC50	Cat	85.41 mg/l, 4.5 Hours
Rat Fat Fat			43.68 mg/l, 6 Hours
Nation		Mouse	> 60000 ppm
51.3 mg/l, 6 Hours Oral LD50 Monkey 6000 mg/kg Mouse 10500 ml/kg 10500 ml/kg Pig >5000 mg/kg 7800 ml/kg Isobutane (CAS 75-28-5) 7800 ml/kg 7800 ml/kg Inhalation 6as 1237 mg/l, 120 Minutes LC50 Mouse 1237 mg/l, 120 Minutes LC50 Rat 1355 mg/l Propane (CAS 74-98-6) Acute 1237 mg/l, 120 Minutes Inhalation LC50 Mouse 1237 mg/l, 120 Minutes LC50 Mouse 1237 mg/l, 120 Minutes Acute 152 %, 120 Minutes 1237 mg/l, 120 Minutes Acute 152 %, 120 Minutes 152 %, 120 Minutes			79.43 mg/l, 134 Minutes
Oral LD50 Monkey 6000 mg/kg Mouse 10500 ml/kg Pig > 5000 mg/kg Rat 10470 mg/kg 7800 ml/kg Isobutane (CAS 75-28-5) 7800 ml/kg Acute Inhalation 4000 ml/kg Gas 1237 mg/l, 120 Minutes LC50 Rat 1355 mg/l Propane (CAS 74-98-6) 4000 ml/kg Acute Inhalation 1237 mg/l, 120 Minutes LC50 Mouse 1237 mg/l, 120 Minutes 52 %, 120 Minutes 52 %, 120 Minutes Facute Inhalation 52 %, 120 Minutes LC50 Mouse 1237 mg/l, 120 Minutes 52 %, 120 Minutes 52 %, 120 Minutes		Rat	> 115.9 mg/l, 4 Hours
LD50 Monkey 6000 mg/kg 10500 ml/kg 10500 ml/kg 2000 mg/kg 2000 mg/kg			51.3 mg/l, 6 Hours
LD50 Monkey 6000 mg/kg 10500 ml/kg 10500 ml/kg 2000 mg/kg 2000 mg/kg	Oral		
Pig		Monkey	6000 mg/kg
Rat 10470 mg/kg 7800 ml/kg		Mouse	10500 ml/kg
Rat 10470 mg/kg 7800 ml/kg		Pig	> 5000 mg/kg
Sobutane (CAS 75-28-5) Acute Inhalation Gas LC50 Mouse 1237 mg/l, 120 Minutes 52 %, 120 Minutes LC50 Rat 1355 mg/l Propane (CAS 74-98-6) Acute Inhalation LC50 Mouse 1237 mg/l, 120 Minutes 1237 mg/l, 120 Minutes LC50 Rat 1355 mg/l LC50 Mouse 1237 mg/l, 120 Minutes		-	
Sobutane (CAS 75-28-5)			
Acute Inhalation Gas LC50 Mouse LC50 Rat Mouse LC50 Rat Mouse LC50 Rat Mouse LC50 Mouse LC50 Rat Mouse LC50 Rat LC50 Rat LC50 LC50 Rat LC50 LC50 Rat LC50 Mouse LC50 LC50 LC50 Mouse LC50 L	Isobutane (CAS 75-28-5)		
Inhalation Gas LC50 Mouse 1237 mg/l, 120 Minutes 52 %, 120 Minutes 52 %, 120 Minutes 1355 mg/l			
Gas LC50 Mouse 1237 mg/l, 120 Minutes 52 %, 120 Minutes 52 %, 120 Minutes 1355 mg/l	· · · · · · · · · · · · · · · · · · ·		
LC50 Rat 1355 mg/l Propane (CAS 74-98-6) Acute Inhalation LC50 Mouse 1237 mg/l, 120 Minutes 52 %, 120 Minutes 1355 mg/l			
LC50 Rat 1355 mg/l Propane (CAS 74-98-6) Acute Inhalation Inhalation LC50 Mouse 1237 mg/l, 120 Minutes 52 %, 120 Minutes 1355 mg/l	LC50	Mouse	1237 mg/l, 120 Minutes
Propane (CAS 74-98-6) Acute Inhalation LC50 Mouse 1237 mg/l, 120 Minutes 52 %, 120 Minutes 1355 mg/l			52 %, 120 Minutes
Acute Inhalation Mouse 1237 mg/l, 120 Minutes LC50 Mouse 52 %, 120 Minutes Rat 1355 mg/l	LC50	Rat	1355 mg/l
Inhalation LC50 Mouse 1237 mg/l, 120 Minutes 52 %, 120 Minutes 52 mg/l Rat 1355 mg/l	Propane (CAS 74-98-6)		
LC50 Mouse 1237 mg/l, 120 Minutes 52 %, 120 Minutes Rat 1355 mg/l	<u>Acute</u>		
52 %, 120 Minutes Rat 1355 mg/l	Inhalation		
Rat 1355 mg/l	LC50	Mouse	1237 mg/l, 120 Minutes
·			52 %, 120 Minutes
658 mg/l/4h		Rat	1355 mg/l
			658 mg/l/4h

^{*} Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Carcinogenicity

Canada - Manitoba OELs: carcinogenicity

ETHANOL (CAS 64-17-5) Confirmed animal carcinogen with unknown relevance to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

3 Not classifiable as to carcinogenicity to humans. d-Limonene (CAS 5989-27-5)

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not likely, due to the form of the product.

12. Ecological information

Very toxic to aquatic life with long lasting effects. **Ecotoxicity**

Components		Species	Test Results
d-Limonene (CAS 598	9-27-5)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia pulex)	69.6 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	0.619 - 0.796 mg/l, 96 hours
Ethyl Alcohol (CAS 64	-17-5)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	7700 - 11200 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	> 100.1 mg/l, 96 hours

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

d-Limonene	4.232
Ethyl Alcohol	-0.31
Isobutane	2.76
Propane	2.36

No data available. Mobility in soil

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents **Disposal instructions**

under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

SDS CANADA

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

TDG

UN number UN1950

UN proper shipping name AEROSOLS, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk -

Packing group Not applicable.

Environmental hazards Yes

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

This product meets the exemption requirements and may be shipped as a limited quantity.

Allowed with restrictions.

IATA

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

Environmental hazards Yes ERG Code 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1950 UN proper shipping name AEROSOLS

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

Environmental hazards

Marine pollutant Yes
EmS F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and the IBC Code

IATA; IMDG; TDG



Marine pollutant



General information IMDG Regulated Marine Pollutant.

15. Regulatory information

Canadian regulations

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other Information

Issue date 07-18-2018

Version # 01

Product name: 0125-0048 ORANGO-WET 1049740002 SDS CANADA

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision information

Product and Company Identification: Alternate Trade Names