

700 XTT / 850 XTT

Hurricane Series

Commercial Automatic Scrubbers



Innovative

Our machines are designed with innovative technologies to increase productivity while lowering the cost of cleaning. The intuitive control panel and superior maneuverability makes it easy to use for any operator.

Large Tank Capacity

The 26/29 gallon capacity tank in a minimum external space makes these models very unique in their category.

Self-Levelling System (SLS)

The automatic brush pressure control allows for constant brush pressure with immediate reaction. This also avoids excessive brush and actuator wear.



Specifications	700 XTT	850 XTT
Model Number	19323-C-AGM	19324-C-AGM
Productivity (<i>Theoretical at max speed</i>)	33, 906 ft ² /hr (3150 m ² /hr)	41,170 ft ² /hr (3825 m ² /hr)
Scrubbing Width	28" (71 cm)	32" (81.5 cm)
Squeegee Width	39" (99 cm)	39" (99 cm)
Numbers of brushes	2 x 14" (2 x 36 cm)	2 x 16" (2 x 41 cm)
Brush/Pad Speed	200 rpm	200 rpm
Brush Motor Power	2 x 500 W	2 x 500 W
Motor Type	3-stages (650 W)	3-stages (650 W)
Water Lift at Squeegee	70" (170 cm)	70" (170 cm)
Traction Motor	Yes	Yes
Solution Tank Capacity	28 Gal (105 L)	28 Gal (105 L)
Recovery Tank Capacity	29 Gal (110 L)	29 Gal (110 L)
Power Supply	24 V (4 x 6 V)	24 V (4 x 6 V)
Maximum Speed	4 km/h	4 km/h
Weight (<i>Without Batteries</i>)	375 lbs (170 kg)	382 lbs (173 kg)
Unit Size (<i>L x W x H</i>)	63" x 29" x 42" (160 x 74 x 108 cm)	65" x 35" x 42" (164 x 88 x 108 cm)
Run Time	4-5 hrs	4-5 hrs
Noise Level	70 dB	70 dB
Approval(s)	N/A	N/A