



OMNI DRY 2.9 amp

(as low as 1.9 amp)

Get the lowest amps with the highest airflow. The 2-speed OmniDry 2.9 delivers 3480 FPM at 2.9 amps, is stackable, features two daisy-chain GFCI outlets, a 25' power cord, and a built-in cord wrap.

❖ High Performance w/ Low Amp Draw

❖ Directional Airflow

← Horizontal

↗ 45° Angle

↑ 90° Angle



SPECIFICATIONS:

Power: 115 VAC, 60 HZ

Drive Motor: 1/3 Horsepower, 2-Speed

Weight: 27 Pounds

Cord: 25 foot

Outlet: Integral GFCI Duplex Power Outlet

Speed	FPM	CFM*	AMPS
HIGH	3480	1150	2.9
LOW	2970	975	1.9

*Maximum Rated CFM 2300



• Balanced airflow for quieter operation

• Lightweight, washable & chemical resistant housing

• Units nest for ease of stacking during storage and handling

• 1 year warranty, 5 year on the housing



ETL Listed - Tested for product safety standards.

3750 - 19th Street NE. Calgary, Alberta, Canada T2E 6V2

Toll Free: 1-800-653-8338 Tel: (403) 291-7050 Fax: (403) 291-0546

www.esteem.com

