High Speed Burnisher





Durable design and excellent performance in a high speed burnisher.

Delivering results

High speed burnishing delivers excellent gloss on a variety of floor finishes. Easily maneuver around furniture, radiators and toe kicks with this unit's low profile base.

Operator comfort and safety

The floating handle easily adjusts to any height operator and allows for comfortable use. The twist grips incorporate a safety lock to ensure operator safety.

Durable construction

Made of durable polyethylene, this rugged unit is able to withstand years of use.

Key Benefits

- Delivers excellent gloss performance on a variety of finished floor surfaces
- Burnisher made of durable corrosion-proof polyethylene
- Floating handle ensures operator comfort





Features	Specifications*
Product Name	BR-1600-NDC (U.S. only) BR-1200-NDC (Canada only - see Approvals below)
Pad Drive System Pad speed burnishing Motor volts Motor HP Motor type Pad diameter Motor amps Pad driver description	1600 rpm / 1200 rpm 120 V 1.5 hp / 1.12 kW Permanent magnet DC, circuit breaker protected 20 in / 510 mm 17 A Flexible disk with centering lock, free floating, accommodates uneven floors
Debris Recovery System Dust control system	_
Productivity Max. coverage (per hour)	10000 ft²/929m²
Dimensions/Weight/Sound level Length Width Height Net weight Sound level (operator's ears)	29.75 in / 755.7 mm 20.75 in / 527.1 mm 49 in / 1244 mm 68 lb / 30.84 kg 70 dBA
Power Cord Power cord length Power cord type	75 ft / 23 m 14 gauge, 3-wire, SJT
Approvals	1600 rpm version not available for sale in Canada. CSA Approved BR-1200-NDC version is available (see Canadian price list for additional information).
Warranty	See your sales representative or authorized distributor for complete warranty details.

^{*}Specifications subject to change without notice