CV570



Compact and easy to handle, CV 570 is built using Structural Foam, making it durable with nothing to rust. It's equipped with convenient carrying handles. Combivac 570 features dual filtration that can be used wet and dry concurrently, without changing filters. CV 570 offer 0.5 micron filtration on dry soil & bull; This unit incorporates our ball float wet shutoff assembly: the ball rotates continually, staying clean and free from debris while preventing water from reaching the motor & bull; It's equipped with a 1200-watt bypass motor providing excellent wet or dry recovery. Complete with a two-year motor warranty.

It's compact, maneuverable and easy to use - an excellent choice where a full-size wet vacuum isn't required.

Tank Capacity	6 gal.	Power Cord Length	42'
Vacuum Motor	1200,1.6 "	Hose Length	
Number of Motors		Pump Power	
Airflow (CFM)	95 cfm	Pump Type	
Waterlift (Inches)	100"	Flow Rate	
Noise Level dB(A)	64 dB(A)	Weight	34 lbs
Head Construction		NaceCare Solutions	
Tank Construction	STRUCTURAL FOAM	1205 Britannia Road Eas Mississauga, Ontario L4W 1C7	^{st,} NACECARE [™]
			NACECARE

(800) 387 3210 TEL (800) 709 2896 FAX

