RSV200



The new design of the RSV series has lead to significant advances in energy consumption as well as overall vacuum performance. They consume 40% less energy than previous models while improving performance by 20%. This is all thanks to the new 680 watt vacuum motor with a 2000+ hour life.

Standard Features:

Back support, waist and shoulder straps have been designed to minimize operator fatigue

CRI approved and LEED-EB compliant

5 year motor warranty

Motor provides 100" waterlift and 120 CFM of airflow 84% soil recovery

Motor life is in excess of 2000 hours

Excellent 0.3 micron filtration at 99.97% efficiency for improved Indoor Air Quality

Standard 4-stage filtration system can be used with or without a bag

Ergonomic ratchet wand that adds up to 6" in length. Hose features swivel fittings to ensure tangle free operation Our new floor tool program improves performance, productivity and ease of use.

| Tank Capacity | 2.5 Gallon | Power Cord Length | 42' |
|--------------------|-----------------------------|---|--------|
| Vacuum Motor | 680W,0.9 hp,1 Stage,1 Speed | Hose Length | 5' |
| Number of Motors | 1 | Pump Power | |
| Airflow (CFM) | 120 CFM | Pump Type | |
| Waterlift (Inches) | 100" | Flow Rate | |
| Noise Level dB(A) | 52 DB(A) | Weight | 12 LBS |
| Head Construction | | NaceCare Solutions | |
| Tank Construction | POLYETHYLENE | 1205 Britannia Road East, Mississauga, Ontario | |



(800) 387 3210 TEL (800) 709 2896 FAX

L4W 1C7

