

TGB1620



Key Features

- 16-gallon solution and recovery tanks
- Fully adjustable flow rate
- Over 3.5 hours of run time powered by 2 maintenance-free gel batteries
- Prolonged battery life with low-voltage shutoff
- Hour meter and battery level indicator
- Tear-away squeegee with quick-release blades for easy cleaning
- Convenient, anywhere charging with the on-board charger

Gel Batteries:

- Safest, most dependable batteries on the market
- Longest-life batteries on the market
- Emit 1/40 of the hydrogen gas of wet lead acid batteries
- Spill-proof and can be charged anywhere

Solution Capacity	16 Gallon
Recovery Capacity	16 Gallon
Cleaning Width	20"
Brush Motor	400 W
Brush Pressure	90 LBS
Brush Size	20"
Brush Speed	150 RPM
Vacuum Motor	400 W, 0.5 HP,
Noise Level dB(A)	65
Battery AH	100AH
Battery Type	2 X 12V (GEL)
Charger	ONBOARD

Chemical Capacity	
Dilution Rate	
Pad Size	20"
Pump Type	
Run Time (max)	3 - 3.5 Hours
Traction Motor	
Traction Speed	
Turning Radius	
Weight	393 LBS
Dimensions (LxWxH)	57"x22"x43"
Working capacity	22,000
Maximum Gradient	

NaceCare Solutions
 1205 Britannia Road East, (800) 387 3210 TEL
 Mississauga, Ontario (800) 709 2896 FAX
 L4W 1C7

